



**ATT-6.5**



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGHT	22,50 IN	571,5 MM
WIDTH	15,75 IN	400,1 MM
HEIGHT	17,00 IN	431,8 MM
WEIGHT	85,3 LBS	38,7 KG
MOTOR	VANGUARD 6.5 4 STROKE	
DISPLACEMENT	203 CC / 4,85 KW / 6,5 BHP	
FUEL TANK CAPACITY	0,95 US GALLON	3,2 LITER
APPROXIMATE RUN TIME	2 HOURS	
ENGINE OIL	SEE VANGUARD OWNER'S MANUAL	
HYDRAULIC PUMP	2 STAGE RADIAL PISTON OVER PISTON	
TOOL OPERATION	2 TOOL SIMULTANEOUS OPERATION	

TECHNICAL SPECS	STANDARD	METRIC
RESERVOIR CAPACITY	0,90 US GALLON	3,4 LITER
MFG. TO NFPA 1936-2020	YES	
SIMULTANEOUS MODE	STANDARD	METRIC
1ST STAGE SETTING	3,200 PSI	220 BAR
1ST STAGE FLOW	245 CU IN/MIN	4,014.8 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	85 CU IN/MIN	1,392.9 CC/MIN
ALTERNATING ACCELERATION MODE (PER TOOL)	STANDARD	METRIC
1ST STAGE SETTING	3,200 PSI	220 BAR
1ST STAGE FLOW	490 CU IN/MIN	8,029.6 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	170 CU IN/MIN	2,785.8 CC/MIN

TNT RESCUE SYSTEMS INC.  
 2490 west Oak Street  
 Ashippun, WI 53003  
[www.TNTRESCUE.com](http://www.TNTRESCUE.com)

