



BT-3.0



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	21,00 IN	533,4 MM
WIDTH	12,00 IN	304,8 MM
HEIGHT	17,10 IN	424,3 MM
WEIGHT	53,20 LBS	24,2 KG
MOTOR	HONDA GX 100 4 STROKE	
DISPLACEMENT	98,00 CC / 2,1 KW / 2,8 BHP	
FUEL TANK CAPACITY	0,32 US GALLON	1,2 LITER
APPROXIMATE RUN TIME	1,3 HOURS	
ENGINE OIL	SEE HONDA OWNER'S MANUAL	
HYDRAULIC PUMP	2 STAGE RADIAL PISTON OVER PISTON	

TECHNICAL SPECS	STANDARD	METRIC
TOOL OPERATION	2 TOOL ALTERNATING OPERATION	
RESERVOIR CAPACITY	0,52 US GALLON	2 LITER
CERTIFIED TO NFPA 1936-2020	YES	
ALTERNATING MODE	STANDARD	METRIC
1ST STAGE SETTING	3,200 PSI	220 BAR
1ST STAGE FLOW	165 CU IN/MIN	2,703.9 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	50 CU IN/MIN	819,4 CC/MIN

TNT RESCUE SYSTEMS INC.
 2490 west Oak Street
 Ashippun, WI 53003
www.TNTRESCUE.com

