



**TWIN-ATT**



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	22.00 IN	558.8 MM
WIDTH	10.30 IN	261.6 MM
HEIGHT	12.39 IN	314.7 MM
WEIGHT	77.00 LBS	34.9 KG
MOTOR	HYDRAULIC PISTON MOTOR	
INPUT MOTOR FLOW	10 GPM	37.9 LPM
MAX. INPUT PRESSURE	3,000 PSI	206.7 BAR
HYDRAULIC PUMP	SINGLE STAGE PISTON OVER PISTON	
HYDRAULIC FLUID	ISO 68 MINERAL BASED	

TECHNICAL SPECS	STANDARD	METRIC
TOOL OPERATION	2 TOOL SIMULTANEOUS OPERATION	
RESERVOIR CAPACITY	0,90 US GALLON	3,4 LITER
MFG. ACCORDING TO NFPA 1936-2020	YES	
SIMULTANEOUS MODE	STANDARD	METRIC
SINGLE STAGE SETTING	10,500 PSI	724 BAR
SINGLE STAGE FLOW	245 CU IN/MIN	4,014.8 CC/MIN
ALTERNATING ACCELERATION MODE (PER TOOL)	STANDARD	METRIC
SINGLE STAGE SETTING	10,500 PSI	724 BAR
SINGLE STAGE FLOW	490 CU IN/MIN	8,029.6 CC/MIN

TNT RESCUE SYSTEMS INC.  
 2490 west Oak Street  
 Ashippun, WI 53003  
[www.TNTRESCUE.com](http://www.TNTRESCUE.com)

